

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 935 232 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
11.08.1999 Bulletin 1999/32

(51) Int Cl.<sup>6</sup>: **G09G 1/16**, H04N 17/04,  
H04N 1/407

(21) Application number: **99300545.3**

(22) Date of filing: **26.01.1999**

**BEST AVAILABLE COPY**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:  
• **Cheung-Mon-Chan, Pascal**  
75013 Paris (FR)  
• **Boutenko, Vladislav**  
92800 Puteaux (FR)

(30) Priority: **05.02.1998 FR 9801356**


(74) Representative: **Szary, Anne Catherine, Dr.**  
London Patent Operation,  
GE International, Inc.,  
Essex House,  
12-13 Essex Street  
London WC2R 3AA (GB)

(71) Applicant: **GE MEDICAL SYSTEMS SA**  
78533 Buc Cedex (FR)

**(54) Method of checking the calibration of a display system**

(57) When the display system is calibrated, digital test image (IMC) delivered as input to system provides a resulting image (IRL) perceived the human eye as be-

ing composed of a plurality individual elements which themselves are composed two grey levels and have the same contrast from element to another.



**FIG\_1**

**EP 0 935 232 A1**

## Description

[0001] The invention relates to the checking of the calibration of a display system. A display system is, for example, a monitor which may or may not be associated with its graphics card or a printer producing a paper proof observed in the light of an office, or a laser reprographics device producing a film observed in a negative viewer, or optionally a combination of several of these display means.

[0002] A display means of a display system, for example connected to a medical imaging apparatus, receives as input a digital image, each point of which is assigned a brightness value (generally between 0 and 255) which will be referred to below by the expression "digital grey level". Each pixel of the image reproduced by the display means then has a brightness level whose value depends on the digital grey level of the corresponding point in the input digital image. The transfer function of a display means is the correspondence law between the input digital grey levels and the output brightness levels.

[0003] A display means is said to be calibrated when its transfer function coincides with a predefined transfer function, called below the "target transfer function".

[0004] Among known calibration methods, mention may be made of those which use generic digital images, i.e. digital images that are independent of the target transfer function and of the observation conditions, in order to test the actual transfer function of a display means. This method of the prior art therefore uses optical density measurements or brightness levels of the various grey levels of these digital test images reproduced by the display means.

[0005] The invention aims to provide a radically different solution to the problems of calibrating display systems.

[0006] According to a first aspect of the invention, there is provided a method of checking the calibration of a display system, characterized in that a visual calibration test pattern intended to be displayed on a display means of the said system and observed by the human eye is generated, this test pattern comprising at least a first part formed by several separate regions each composed of a first area having a first light level and a second area having a second light level, all the light levels being different from one another and the difference between the two levels of the two areas of a region being predetermined and the same for all the regions, an overall transfer function is determined from a first predefined transfer function of the calibrated display system and a second predefined transfer function from a mathematical model of the human visual system, a digital calibration image corresponding to the said calibration test pattern is determined from the said visual calibration test pattern and from the inverse of the said overall transfer function, the said digital calibration image is delivered as input to the display system and the resulting image

thus obtained is displayed on the said display means, and the calibration of the display system is checked by displaying the said resulting image.

[0007] According to a second aspect of the invention, there is provided a method of checking the calibration of a printer forming, with a display system, for example a monitor, a display system connected to common processing means, in which a visual calibration test pattern intended to be displayed on the display means and on the printer and observed by the human eye is generated, this test pattern comprising at least a first part formed by several separate regions each composed of a first area having a first light level and a second area having a second light level, all the light levels being different from one another and the difference

[0008] One embodiment of the invention provides a means of checking the calibration of a display system which is rapid and requires no direct measurement or, at the very least, only a very small number of direct measurements.

[0009] The invention therefore proposes to generate, for given observation conditions and for a given target transfer function, a digital test image the only observation of which by the human eye under these given observation conditions is sufficient to determine whether the actual transfer function of the display system coincides with its target transfer function (i.e. the transfer function of the calibrated system) and therefore to determine whether the system is correctly calibrated.

[0010] More specifically, according to a general characteristic of the invention, when the transfer function of the display system coincides with the target transfer function, the digital test image used in the present invention is perceived by the human eye as being composed of a plurality of individual elements which themselves are composed of two levels, for example two grey levels, and have the same contrast between these two levels from one element to another.

[0011] In other words, the invention provides a method of checking the calibration of a display system, in which a visual calibration test pattern intended to be displayed on a display means of the said system and observed by the human eye is generated, this test pattern comprising at least a first part formed by several separate regions each composed of a first area having a first light level (for example, the first grey level) and a second area having a second light level (for example, the second grey level), all the light levels being different from one another and the difference between the two levels (contrasts) of the two areas of a region being predetermined and the same for all the regions.

[0012] An overall transfer function is determined from a first predefined transfer function of the calibrated display system (target transfer function) and a second predefined transfer function from a mathematical model of the human visual system.

[0013] A digital calibration image corresponding to the said calibration test pattern is determined from the said

visual calibration test pattern and from the inverse of the said overall transfer function.

**[0014]** The said digital calibration image is delivered as input to the display system and the resulting image thus obtained is displayed on the said display means, and the calibration of the display system is checked by displaying the said existing image.

**[0015]** In other words, the digital levels, which are delivered as input to the display system, are determined from the levels which should actually be perceived by the human brain when the calibration test pattern is observed under predetermined observation conditions and when the transfer function of the display system coincides with the target transfer function, that is to say when the system is calibrated. These digital input levels are determined by inverting the combination of the target transfer function of the display system and of the transfer function of the human visual system for these observation conditions. Several mathematical models of the human visual system are well known and available to those skilled in the art (such as, for example, the Barten model) for determining the transfer function of the human visual system.

**[0016]** The target transfer function of the display system may, for example, be generated beforehand in a conventional manner using, for example, optical density brightness level measurements. The Measurements or invention then makes it possible, in particular when the display signal simply consists of a monitor or a display screen, the target transfer function of which is known beforehand, to then check any subsequent calibration of the monitor by simply displaying the calibration test pattern.

**[0017]** This being so, the invention applies particularly advantageously to the checking of the calibration of a printer connected, for example with a monitor, to common processing means. Mention may be made, for example, of a printer and of a monitor which are connected to the output of the same medical imaging system.

**[0018]** Thus, in an embodiment of the invention, a visual calibration test pattern intended to be displayed on the display means (for example the monitor) and on the printer and which is to be observed by the human eye is generated. This test pattern has the same features as those which have just been described above. However, an overall transfer function of the display system is determined from a first predefined transfer function of the calibrated monitor (target transfer function of the monitor) and from a second predefined transfer function of a mathematical model of the human visual system. The digital calibration image corresponding to the said calibration test pattern is also determined from the said calibration test pattern and from the inverse of the said overall function. The said digital calibration image is delivered as input to the display system and the resulting image thus obtained is printed by the printer. The calibration of the printer is then checked by displaying the said resulting image.

**[0019]** In other words, the invention here makes it possible, using the said calibration test image, to check the calibration of a printer using another calibrated display means, for example a monitor.

**[0020]** When the discretization increment display system is smaller than the visual detection threshold of the human eye, of the contrast a visual calibration test pattern is advantageously generated which has a first part associated with a first constant difference in light level (constant difference in contrast for all the elements of the test pattern) smaller than the said visual detection threshold and which also has a second part that is structurally similar to the first part and associated with a second constant difference in light level greater than the said visual detection threshold.

**[0021]** In other words, when the display means have a smaller discretization increment than the detection threshold of the human visual system, a test pattern composed of two subpatterns is used. The contrast of the two elements of the first subpattern is chosen to be slightly lower than the detection threshold of the human visual system, while the contrast of the elements of the second subpattern is chosen to be slightly higher than the detection threshold of the human visual system.

**[0022]** In this variant, the system may be tested by contrasts of the elements of if the contrast of one of subpattern can be perceived, least one of the elements cannot be perceived, it may calibration of the display observing the perceived the two subpatterns. Thus, the elements of the first or if the contrast of at of the second subpattern then be concluded that the system is not correctly calibrated.

**[0023]** When the discretization increment display system is greater than the visual detection threshold of the human eye, a visual calibration test pattern comprising only the said first part is generated and a constant difference in visual level significantly greater than the said discretization increment, for example equal to three or four times this increment, is then chosen. Thus, if the various perceived contrasts of the various elements of the test pattern are not constant, but change from one element to another, it may be concluded from this that the system is not correctly calibrated.

**[0024]** In the variant of the invention relating to the printer connected, with the monitor, to the medical imaging system, the various elements of the selection of the characteristics of the printer are generated, especially its discretization increment, but the inverse target transfer function of the monitor is used to define the digital calibration image from the visual calibration test pattern.

**[0025]** The invention will now be described in greater detail by way of drawings, in which:-

Figure 1 illustrates, very diagrammatically, an image perception chain,

Figure 2 illustrates, very diagrammatically, a cali-

bration check according to the invention using a calibration test pattern,

Figures 3 and 4 illustrate, very diagrammatically, a calibration test pattern which can be used in a first variant of the invention,

Figure 5 illustrates a digital test image corresponding to the calibration test pattern of Figure 4,

Figure 6 illustrates, very diagrammatically, the generation of a visual calibration test pattern according to a second variant of the invention, and

Figure 7 illustrates a curve showing the differences between the actual contrast and the desired contrast,

#### DETAILED DESCRIPTION OF THE INVENTION

**[0026]** In Figure 1, the label DR denotes a medical imaging system delivering digital images, each composed of a plurality of points each assigned a digital value, typically between 0 and 255, and representative of a digital grey level NGN, to a display system SAF (which may be composed of a single display monitor MN or else the monitor MN and a printer IMP which are connected together to this system DR).

**[0027]** The display system then delivers an image which may be displayed on the screen or printed on the printer IMP and each pixel of which, corresponding to each input point (digital input value), is assigned a brightness level NL. The image is perceived by the human visual system OL and the human brain then perceives a perceived grey level NGP for each brightness level.

**[0028]** It is assumed in a first application of the invention that the display system SAP is composed only of the monitor MN.

**[0029]** The method of checking the calibration according to the invention consists, as illustrated more particularly in Figure 2, in generating a digital test image IMC from a visual display test pattern MRC and from an overall transfer function inverted in processing means MT. This digital test image or digital calibration image IMC is then delivered as input to the display system SAF and is reproduced by the display screen, for example. The human brain then perceives a resulting perceived image IRL.

**[0030]** According to a first variant of the invention (Figures 3 and 4), a plurality (n) [lacuna] elements ELi, each composed of two perceived grey levels NGPi0 and NGPi1, are defined on the scale of grey levels perceived by the human brain. The difference between these two levels, that is to say the contrast of each element ELi is constant and the same for each of the elements. On the other hand, all the levels NGPi are different from one another.

**[0031]** Based on this definition of the n elements ELi, a visual calibration test pattern MRC is defined which here is composed only of a first part formed from several (n) separate regions which are also labeled ELi. Each of these regions corresponds to an element ELi of the scale of perceived grey levels. Each region ELi is composed of a first area Zi0 having a first light level, that is to say a first perceived grey level NGPi0, equal to that of the element ELi defined in Figure 3 and of a second area Zi1 having the grey level NGPi1.

**[0032]** In this figure, square areas have been shown. Of course, any other shape of area, such as, for example, circular areas, could have been used.

**[0033]** An overall transfer function is then determined from the combination of the target transfer function of the monitor, that is to say the transfer function of the calibrated monitor, and from a transfer function derived from a mathematical model of the human visual system. This transfer function of the human visual system makes it possible to associate a perceived grey level with each brightness level. There are many mathematical models of the human visual system available to those skilled in the art. Thus, mention may be made of the so-called Barten model described, for instance, in the article by P. G. J. Barten: "Physical model for the Contrast Sensitivity of the human eye"; Proc. SPIN 1666, 57-72 (1992) and "Spatio-temporal model for the Contrast Sensitivity of the human eye and its temporal aspects", Proc. SPIE 1913-01 (1993).

**[0034]** Mention may also be made, for example, of the Hunt model (R. W. G. Hunt, "Revised colour-appearance model for related and unrelated colours", Color Res. Appl. 16, 146-165 (1991),

- the Bartelson and Breneman model
- (C. J. Bartelson and E. J. Breneman, "Brightness perception in complex fields". J. Opt Soc. Am. 57, 953-957 (1967),
- the Daly local conical model (S. Daly, "The visible differences predictor: An algorithm for the assessment of image fidelity", taken from the work: in Digital Images and Human vision, A.B. Watson, Ed. Chapter 14, MIT Press, Boston, 1993,
- the Weber-Fechner law, particularly known to those skilled in the art.

**[0035]** Next, the overall transfer function is inverted, in a conventional and known manner, so as to obtain an inverted transfer function, that is to say a transfer function associating a digital grey level of a point in a digital calibration image with each perceived grey level of a pixel of the visual calibration test pattern

**[0036]** The digital calibration image IMC illustrated in Figure 5, and corresponding to the virtual calibration test pattern, is then generated. This digital calibration image

IMC is defined, in a manner similar to the visual calibration test pattern, by a plurality of digital regions  $ELC_i$  each composed of a first area  $ZCi0$  and of a second area  $ZCi1$ . All the pixels of the first area are assigned a digital grey level  $NGNi0$  and all the pixels of the second area are assigned a digital grey level  $NGNi1$ .

**[0037]** The calibration test pattern as defined in Figures 3 and 4, and consequently the corresponding digital calibration image IMC, is especially used when the discretization increment of the monitor is greater than the contrast detection threshold of the human eye. Elements  $EL_i$  will then be chosen whose contrast, that is to say the difference in perceived grey levels, is significantly greater than the discretization increment, for example equal to three or four times this increment. The fact that a contrast significantly greater than the discretization increment is chosen makes it possible to minimize the impact of the variation in this discretization increment along the scale of perceived grey levels. However, it is possible to choose smaller contrasts if the scale of perceived grey levels is divided into areas within which the discretization increment remains approximately constant.

**[0038]** If the discretization increment of the display system is smaller than the contrast detection threshold of the human eye, a visual calibration test pattern composed in fact of two parts (Figure 6) will be defined. More specifically, the first part will be composed of  $n$  elements  $ELAi$ , each contrast of which is less than the contrast detection threshold SPR of the human eye. The second part PB will consist of  $n$  elements  $ELBi$ , the contrast of which will be chosen to be greater than the threshold SPR. In practice, a contrast slightly less than the threshold SPR, for example 0.8 or 0.9 times this threshold, will be chosen for the elements  $ELAi$ , whereas a contrast slightly greater [lacuna] SPR (for example 1.1 or 1.2 times this threshold) will be chosen for the elements  $ELBi$ .

**[0039]** Each of the parts PA and PB will therefore be composed of an image similar to that illustrated in Figure 4. The corresponding complete display test pattern would, if it were fully perceived by the eye, be equal to the juxtaposition of two test patterns such as those illustrated in Figure 4

**[0040]** Figure 7 shows, in the in the actual solid line, the variation in the actual contrast of the various elements of the image IRL actually perceived by the human eye, compared with the desired contrast of these same elements, that is to say the contrast of these elements as they ought to be perceived in the visual calibration test pattern if the system were correctly calibrated.

**[0041]** If the system is correctly calibrated, the curve of correspondence between the actual contrast and the desired contrast is in fact the straight line passing through the origin with a slope of  $45^\circ$ , as illustrated by the dotted line in Figure 7.

**[0042]** However, this Figure 7 shows that when the slope of the curve is greater than  $45^\circ$  the contrast of the

element  $EL_i$  is in fact increased (actual element  $EL_{10}$ ). However, when the slope of the curve is less than  $45^\circ$  the contrast of an element  $EL_2$  is decreased (element  $EL_{20}$ ).

**[0043]** From this observation, and if reference is more particularly made to a visual calibration test pattern such as that used in the variant in Figure 6, it may be observed that if the slope of the actual curve in Figure 7 is equal to  $45^\circ$  the contrast of an element of the first part PA of the test pattern is not perceived by the human eye, whereas the contrast of the corresponding element of the second part PB is perceived.

**[0044]** When the slope of the actual curve is significantly greater than  $45^\circ$ , the contrast of the two corresponding elements of the first part PA and of the second part PB of the test pattern may be perceived. However, when the slope of the actual curve is significantly less than  $45^\circ$ , the contrast of neither of the two corresponding elements not of the first part PA and of the second part PB of the test pattern may be perceived. Consequently, the calibration of the display system, that is to say in this case the calibration of the monitor but also the calibration of the printer, may be checked by observing the perceived contrast of the elements of the two parts PA and PB. If the contrast of at least one of the elements of the first part PA can be perceived, or if the contrast of at least one [lacuna] of the second part PB cannot be perceived, it may then be concluded that the display system is not calibrated. If the contrast of all the elements of the first part PA cannot be perceived, and if the contrast of all the elements of the second part PB can be perceived and if the actual transfer function of the display system is assumed to coincide with the target transfer function, at least at one point, it may be concluded that the display system is calibrated. If it is not known that this coincidence between the actual transfer function [lacuna] the target transfer function exists at a point, it will then be necessary to take a direct calibration measurement at a point, for example on a black level, to ensure that the system is properly calibrated. For example, a direct measurement of the brightness or of the optical density may be taken for this particular point and this measurement may be compared with a calibration reference.

**[0045]** If a visual calibration test pattern is used like the one illustrated in Figures 3 and 4, that is to say a test pattern for which the contrast at each element is significantly greater than the discretization increment, the calibration of the system may be checked by observing the perceived contrast of the various elements. If the perceived contrast of the various elements is not constant but changes from one element to another, it may then be concluded that the display system is not calibrated. If the contrast of all the elements is constant, and if the actual transfer function of the display system is assumed to coincide with the target transfer function, at least at two points, it may be concluded from this that the system is calibrated. If it is not known for certain that

this actual transfer function coincides at two points with the target transfer function, it is then necessary to take two direct calibration measurements in order to reach the conclusion that the system is correctly calibrated.

[0046] It will now be assumed, in a second application of the invention, that the display system SAP is composed of the monitor MN and the printer IMP which are connected together to the medical imaging system DR.

[0047] The various elements of the test pattern MRC, especially the contrasts and the minimum and maximum values of the grey levels, depending on the characteristics of the printer and in particular on its discretization increment, are then generated.



[0048] This being so, the inverted target transfer function of the monitor is used to define the digital calibration image IMC from the test pattern MRC.

## Claims


1. A method of checking the calibration of a display system, characterized in that a visual calibration test pattern (MRC) intended to be displayed on a display means of the said system and observed by the human eye is generated, this test pattern comprising at least a first part (PA) formed by several separate regions (ELI) each composed of a first area (ZiO) having a first light level and a second area (ZiI) having a second light level, all the light levels being different from one another and the difference between the two levels of the two areas of a region being predetermined and the same for all the regions, an overall transfer function is determined from a first predefined transfer function of the calibrated display system and a second predefined transfer function from a mathematical model of the human visual system (OL), a digital calibration image (IMC) corresponding to the said calibration test pattern is determined from the said visual calibration test pattern and from the inverse of the said overall transfer function, the said digital calibration image is delivered as input to the display system and the resulting image thus obtained (IRL) is displayed on the said display means, and the calibration of the display system is checked by displaying the said resulting image.
2. A method of checking the calibration of a printer forming, with a display system, for example a monitor (MN), a display system connected to common processing means, in which a visual calibration test pattern (MRC) intended to be displayed on the display means (MN) and on the printer (IMP) and observed by the human eye is generated, this test pattern comprising at least a first part (PA) formed by several separate regions each composed of a first area having a first light level and a second area having a second light level, all the light levels being dif-

ferent from one another and the difference between the two levels of the two areas of a region being predetermined and the same for all the regions, an overall transfer function is determined from a first predefined transfer function of the calibrated monitor and from a second predefined transfer function of a mathematical model of the human visual system, a digital calibration image (IMC) corresponding to the said calibration test pattern is determined from the said visual calibration test pattern and from the inverse of the said overall transfer function, the said digital calibration image is delivered as input to the display system and the resulting image thus obtained is printed by the printer (IMP), and the calibration of the printer is checked by displaying the said resulting image.


3. Method according to claim 1 or 2, characterized in that, the discretization increment of the display system being smaller than the visual contrast detection threshold (SPR) of the human eye, a visual calibration test pattern is generated which has a first part (PA) associated with a first constant difference in light level smaller than the said visual detection threshold and which also has a second part (PB) that is structurally similar to the first part and associated with a second constant difference in visual level greater than the said visual detection threshold.
4. Method according to claim 1 or 2, characterized in that, the discretization increment of the display system being greater than the visual contrast detection threshold (SPR) of the human eye, a visual calibration test pattern comprising only the said first part is generated and in that the constant difference in visual level is significantly greater than the said discretization increment, for example equal to 3 or 4 times this increment.




FIG\_3




FIG\_4




FIG\_5



FIG\_7



FIG\_6





European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 30 0545

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X A	EP 0 750 431 A (EASTMAN KODAK CO) 27 December 1996 * abstract * * page 3, line 9 - line 35 * * page 4, line 3 - page 5, line 42 * * page 7, line 16 - page 9, line 47 * * figures 1,2,11 * ---	1,2 3,4	G09G1/16 H04N17/04 H04N1/407
A	EP 0 542 012 A (EASTMAN KODAK CO) 19 May 1993 * abstract * * page 2, line 1 - page 3, line 55 * * figures 1-10 *	1-4	
A	US 2 380 244 A (LOYD A. JONES ET AL) 10 July 1945 * page 1, column 2, line 36 - page 2, column 1, line 52 * * page 3, column 1, line 4 - line 75 * * figures 2-4,6,7 * ---	1-4	
A	GRAY J E: "ACCEPTANCE AND USE OF THE SMPTE MEDICAL DIAGNOSTIC IMAGING TEST PATTERN FOR TELEVISION MONITORS AND HARD-COPY RECORDING CAMERAS" SMPTE JOURNAL, vol. 99, no. 12, 1 December 1990, pages 1001-1007, XP000172375 * abstract * * page 1002, column 1, line 31 - page 1007, column 1, line 17 * * figures 1,2 * -----	1-4	TECHNICAL FIELDS SEARCHED (Int.Cl.6)  G09G H04N G06K
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>27 April 1999</b>	Examiner <b>Cochonneau, O</b>
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons Δ : member of the same patent family, corresponding document</p>			

FPO FORM 1503 03.87 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 0545

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

27-04-1999

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP 0750431	A	27-12-1996	US	5754222 A	19-05-1998
			JP	9018902 A	17-01-1997
EP 0542012	A	19-05-1993	US	5369499 A	29-11-1994
			JP	6070274 A	11-03-1994
US 2380244	A	10-07-1945	NONE		

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☐ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**